

5 Inch LCD Customer Display

(M/N:OCPD-LCD500)



Features:

- ❖ Support OPOS driver
- ❖ Compatible with 15 kinds command, like ESC/POS, CD5220 and so on..
- ❖ Compatible with 20 countries Languages, other languages can be customized
- ❖ Provide custom setup software all customizations can be done by the end user
- ❖ Support setting booting image
- ❖ Three display areas can setting background color and character color
- ❖ Top display area can setting logo and fixed characters
- ❖ The middle display area can be switched to 2*20 characters or 4*20 characters display
- ❖ The bottom display area supports custom scrolling play characters

Data sheet:

General	Display Method	TFT - LCD Display (5 inch COLOR PANEL)
	Number of characters	40 character(20columns×2line)/ 80 character(20columns×4 line)
	Brightness	> 350cd/m2
	Resolution	480*272 or 800*480
	Character font	24*48/40*80 dot matrix
	Character type	95 Alphanumeric, 32 international characters
	Character size	8 (H) ×5.25 (W) mm

Specifications are subject to change without prior notice.

Together We Quest For The Best

	Dot size (X×Y)	0.23×0.23mm
	Panel Dimension	113.5 (L) mm×65.5 (W) ×40 (H)
	Pole Dimension	Per support length: 163 (L) ×27.65 (DIA) mm/ 80 (L) ×27.65 (DIA) mm
	Base Dimension	126 (L) ×89 (W) ×13.5 (H) mm
	Viewing Angle	Max.135°
	Horizontal Rotation	Max.355°
	Weight	490 grams/506grams
Commands Mode		15 kinds, E.g LD220, ESC/POS, AEDEX, UTC/S, UTC/P, ADM788, DSP800, CD5220, EMAX, LOGIC CONTROL etc
Language Support		CP437, Katakana, CP850, CP860, CP863,CP865, WCP1252, CP857, WCP1250, WCP1253,WCP1255, WCP1251, CP866, CP852, CP737, CP858, CP864,WCP1257, WCP1258 , Tai (CP874)
Interface		RS-232 (serial) /USB
Connection	Baud	Direct connection 9600/19200/38400/57600/115200 bps
Reliability	MTBF	30000 hours
Power	Consumption	5-24 VDC
Safety	EMC standards	FCC, CE, ROHS
	Safety standards	